

100% Money Back
Guarantee

Vendor:Cisco

Exam Code:500-451

Exam Name:Enterprise Networks Specialization

Version:Demo

QUESTION 1

Which step is one of the typical configuration steps when configuring Flow Exporter for Prime Infrastructure 2.0 or higher?

- A. Set the IP address to export the Flexible NetFlow cache entry to a destination system.
- B. Configure the source IP address interface for each interface part of Flexible NetFlow exporter.
- C. Configure the TCP transport protocol and a TCP port number 1991 for a Flexible NetFlow flow exporter.
- D. Configure the TCP transport protocol and a TCP port number 9991 for a Flexible NetFlow flow exporter.

Correct Answer: A Question Set 8

QUESTION 2

A customer wants to dynamically monitor the status of a critical route. Which feature should you recommend that the customer use?

- A. Wireshark
- B. Embedded Event Manager
- C. IP Service Level Agreement
- D. Generic Online Diagnostics

Correct Answer: C

QUESTION 3

Which feature is used on the Catalyst 6500 Series Switch for real-time traffic capture and decoding?

- A. Lancope Lite
- B. Packet Monitor
- C. Mini Protocol Analyzer
- D. Inline Wireshark module

Correct Answer: C

QUESTION 4

A network administrator is using the Embedded Event Manager, which is supporting multiple actions initiated from the script. Which two policy actions can be used within the EEM? (Choose two)

- A. Execute a Tcl script.
- B. Send an email.
- C. Run another policy.
- D. Hot swap the supervisor.
- E. Manually send an SNMP trap.

Correct Answer: BC Testlet 1

TESTLET OVERVIEW

Title: Case Study

The following testlet will present a Case Study followed by [count] multiple choice question(s), [count] create a tree question(s), [count] build list and reorder question(s) and [count] drop and connect question (s).

You will have [count] minutes to complete the testlet.

For help on how to answer the questions, click the Instructions button on the question screen.

QUESTION 5

Within Cisco ISE, which persona or node is responsible for enforcing policy?

- A. Policy Administration Node
- B. Guest Service persona
- C. Inline Posture Node
- D. Policy Service persona

Correct Answer: C

QUESTION 6

How can you customize the Home view of Prime Infrastructure?

- A. Open the Administration menu, select the Dashlets option, select new Dashlet, click Add to Home View.
- B. Open the Operate menu, select the Home View option, Choose Edit Home View, select new Dashlet from the list.
- C. Add Dashlets and edit existing Dashlets.
- D. Home view cannot be customized in Prime Infrastructure 2.0.

Correct Answer: C

QUESTION 7

When configuring the RADIUS server between ISE and the network access device, there are many different types of NADs. Which option is the NAD?

- A. Cat2960 Access Switches
- B. CAP-3600 Access Point in Local mode
- C. CT 5508 Wireless LAN Controller
- D. Cisco Prime Infrastructure
- E. AnyConnect wireless client

Correct Answer: C

QUESTION 8

When a user gets redirected to the device registration portal, which important information field is prepopulated by ISE?

- A. user\'\'s username
- B. user\'\'s first and last name
- C. device ID with IP address
- D. device ID with MAC address

Correct Answer: D

QUESTION 9

Which action is required when configuring Flexible NetFlow on a Cisco Catalyst switch?

- A. Configure the flow descriptor.
- B. Configure the flow exporter.
- C. Configure the flow importer.
- D. Configure the flow reset target.

Correct Answer: B

QUESTION 10

Within Cisco ISE, which persona or node handles RADIUS requests and the Sponsor and Guest portals?

- A. Policy Administration Node
- B. Guest Service persona
- C. Policy Service persona
- D. Monitoring persona

Correct Answer: C

QUESTION 11

When building the Security Group Egress Policy Matrix, what is the default policy regarding empty intersecting cells?

- A. enabled, SGACLs : permit IP
- B. enabled, SGACLs : deny IP
- C. disabled, SGACLs : permit IP
- D. disabled, SGACLs : deny IP

Correct Answer: A

QUESTION 12

In the Converged Access solution, how does the controller display the access point name when there is no existing configuration for the AP?

- A. AP+IP address dotted decimal, for example, AP10.10.1.1
- B. AP+Ethernet MAC Address, for example, AP44d3:ca42.4337
- C. AP+IP address in hex, for example, AP0A.0A.01.01
- D. AP+Base Radio MAC Address, for example, AP18.33.9d.f1.40.50

Correct Answer: B