

100% Money Back
Guarantee

Vendor:Huawei

Exam Code:H31-211

Exam Name:Huawei certified Network Associate -
HCDA (Carrier IP)

Version:Demo

QUESTION 1

The requirements for OSPF protocol deployment in network planning are correct (multiple choice)? (multiple choice)

- A. Select the IP address of the loopback0 interface as the router ID.
- B. Select a high-performance router as the DR/BDR in the network segment.
- C. Ensure that the backbone area (Area 0) is physically continuous and does not use virtual links (Virtuallink).
- D. Select a device with high-performance processor memory in the network as the ABR

Correct Answer: ABCD

QUESTION 2

Which configuration method can be used to add the trunk port ethernet0/1 of the switch to VLAN 4? (multiple choice)

- A. [Switch]vlan 4 [Switch-vlan4]port ethernet 0/1
- B. [Switch]vlan 4 [Switch-Ethernet0/1]port trunk pvid vlan 4
- C. [Switch]vlan 4 [Switch-vlan4]port trunk ethernet 0/1
- D. [Switch]vlan 4 [Switch -Ethernet0/1]port trunk permit vlan 4

Correct Answer: ABD

QUESTION 3

Which of the following devices are working at the network layer?

- A. Hub
- B. Bridge
- C. Switch
- D. Router

Correct Answer: BC

QUESTION 4

In order to expand the network range, what equipment can I use to connect multiple cables, recover the distorted signal, and amplify the signal?

- A. Hub

- B. Repeater
- C. Switch
- D. Router

Correct Answer: B

QUESTION 5

The characteristics of dynamic ECMP equal-cost routes are ()? (multiple choice)

- A. Protocol is the same
- B. Preference is the same
- C. Cost is the same
- D. Mask is the same

Correct Answer: ABC

QUESTION 6

If a switch displays part of the information as follows, what is the PVID of this port? [Quidway] display interface Ethernet 1/0/1...Mdi type:autoPort link-type:accessTagged VLAN ID:noneUntagged VLAN ID:5

- A. 0
- B. 1
- C. 5
- D. Insufficient information, unknown

Correct Answer: C

QUESTION 7

Which parameters must be specified to configure a static MAP in a Frame Relay package? (multiple choice)

- A. Local DLCI
- B. Peer DLCI
- C. Local protocol address
- D. The protocol address of the peer

Correct Answer: AD

QUESTION 8

Regarding the process of terminal users accessing the Internet, what are the correct descriptions below? (multiple choice)

- A. The user initiates an Internet access request, and the Layer 2 device of the access network establishes a Layer 2 connection for the user and transparently transmits the request to the upper BRAS device.
- B. The access network does not control the user, but simply establishes a Layer 2 connection to transparently transmit user information to the upper device.
- C. SR is responsible for the authentication, authorization, and assignment of IP addresses to users.
- D. After the user authentication succeeds, the BRAS routes the user packet to the upstream device, that is, the aggregation layer device.

Correct Answer: ABD

QUESTION 9

Which of the following devices work at the physical layer?

- A. Switch
- B. Hub
- C. Router
- D. Firewall

Correct Answer: B

QUESTION 10

A switch that uses STP, its one port goes from the learning state to the forwarding state to go through a forwarding delay. By default, how many seconds is the forwarding delay?

- A. 10
- B. 15
- C. 20
- D. 30

Correct Answer: B

QUESTION 11

The following is true about the routing self-loop description in an OSPF network?

- A. Route self-loop has been eliminated in the OSPF area;
- B. There is no route self-loop between OSPF areas.
- C. The routing self-loop is not eliminated in the OSPF autonomous system.
- D. There is no self-loop in the external route of the OSPF autonomous system.

Correct Answer: A

QUESTION 12

In the OSI model, which of the following is the correct description of the physical layer function?

- A. Ensure that the data is transmitted correctly.
- B. Determine how packets are forwarded and routed
- C. Transmitting the bit stream on the channel
- D. Error correction and flow control

Correct Answer: C